

Bayesian network example

Andrea Passerini
passerini@disi.unitn.it

Bioinformatics


A toy regulatory network

Conditional probability tables

- Genes *A* and *B* have independent prior probabilities:

gene	value	P(value)
A	active	0.3
A	inactive	0.7

gene	value	P(value)
B	active	0.3
B	inactive	0.7



- Gene *C* can be enhanced by both *A* and *B*:

		A			
		active		inactive	
		B		B	
		active	inactive	active	inactive
C	active	0.9	0.6	0.7	0.1
C	inactive	0.1	0.4	0.3	0.9

A toy regulatory network


Probability of A active (1)

- Prior:

$$P(A = 1) = 1 - P(A = 0) = 0.3$$

- Posterior after observing active C:

$$P(A = 1|C = 1) = \frac{P(C = 1|A = 1)P(A = 1)}{P(C = 1)} \simeq 0.514$$



Note


The probability that A is active *increases* from observing that its regulated gene C is active

A toy regulatory network

Probability of A active

- Posterior after observing that B is also active:

$$P(A = 1 | C = 1, B = 1) = \frac{P(C = 1 | A = 1, B = 1)P(A = 1 | B = 1)}{P(C = 1 | B = 1)} \simeq 0.355$$



Note

- The probability that A is active *decreases* after observing that B is also active
- The B condition *explains away* the observation that C is active
- The probability is still greater than the prior one (0.3), because the C active observation still gives some evidence in favour of an active A